




# C-PURE 750™ Smoke Evacuation System



CIMPAX® C-PURE 750™  
Smoke Evacuation System for  
Removal of Laser and Electrosurgical Smoke

CIMPAX® C-PURE 750 Combining simplicity and ultra-quiet operation in a compact package, the C-PURE 750 Surgical Smoke Evacuation System exceeds expectations for value and efficacy. The unique 3-port filter offers a variety of options when choosing an accessory to meet the clinical need. C-PURE 750 is designed to be simple to use, flexible in its options for tubing and accessories, and sets new precedents for quiet operation. Providing effective surgical smoke evacuation that encompasses 4 layers of filtration and up to 35 hours of filter life, the C-PURE 750 will deliver the performance necessary to effectively manage surgical smoke plume with unsurpassed value. Operate with Remote Sensor Activator, control panel, or a footpedal.

- Compact design allows for easy placement on a shelf or counter and accommodates stack-ability
- Quiet, yet powerful operation will assist in providing a safe operating environment without disruption
- 35 hour maximum filter life delivers unsurpassed value and reduces per procedure costs
- 3-port filter design puts the power of hose and accessory options in your hand and eliminates adapters
- Filter ports are covered for additional safety
- Simplicity reduces training needs and enhances utilization



#### Ordering information

<b>C-PURE 750</b> 230VAC±10% 50Hz/60Hz Dim.:15.2cm H x 27.9 cm W x 39.4 cm D, Weight: 4.5kgs	Ref. C32-01-750
<b>Sensor</b> for automatic remote activation of C-PURE 750 with 2-10 seconds time delay option.	Ref. C32-10-002
<b>Ulpa/Carbon Filter</b> for C-PURE 750 with 22/9,5/6,4mm connection, Maximum Filter Life: 35 hours	Ref. C32-25-001

#### Accessories

<b>C-VAC TORNADO™</b> Integrated smoke evacuation pencil 4 meter lead, PVC and phthalate free ESU cable with UIS-3-pin connector and 3 meter PVC and phthalate free tubing with combined 9,5/15/22mm connector. Single use.	With 70 mm standard blade electrode	Ref. C31-19-001
	With 70 mm coated blade electrode	Ref. C31-19-101
	Extender Suction tip, box of 25 pcs., sterile	Ref. C31-15-145